Difussion 1
Bollard Light

IP 65




AG LIGHTING





| Item | Height(mm) | Light Source | Input Voltage(V) | Operating Current(MA) | Consumption(W) | Luminance(LM) | IK |
|---|---|---|---|---|---|---|---|
| AGXDLD4234A | 300 | 42×0.2W | DC 24 120/ 240 | DC 24V=415<br>120V=76<br>240V=38 | DC 24=10<br>120=8.6<br>240=8.2 | 586 | 07 |
| AGXDMD4234A | 550 | | | | | | |
| AGXDHD4234A | 800 | | | | | | |




Unit: mm

## Specification

| | |
|---|---|
| Housing | ADC 12# Die-casting aluminum powder coated.<br>T=60-80μm Adhesion of ISO class 1/ASTM class 4B |
| Light Window | PMMA |
| LED Type | SMD |
| LED Driver | Built in on/off driver |
| Operating Temperature | -20˚C~40˚C |
| Power Cable | Outside of luminaire (Without waterstopper)<br>12V/24V: H05RN-F 2×1.0mm², L=0.5m<br>120V/240V: H05RN-F 3×1.0mm², L=0.5m |
| Base | Flange base |
| Dimming Support | External DALI supported TRIAC,0-10V,<br>PWM via external driver on request |

## Painting Color

Primary

Sanded Black
RAL 9005

Secondary

Sanded Dark Grey
KAP 7037




Sanded Bronze
KAP 7008

Modular Light Source and Power with IP-66




1. IP66 light Source module with pc cover
2. IP66 built-in power module
3. IP67 cable gland

## Base & Accessories

| Surface Mounting Base | Inground Base(Optional) | Ground Anchor Base(Optional) |
|---|---|---|
|  Type A<br>Flange Base Non-Detachable |  C3001 |  22A |
|  Type B<br>Non-flange Base Detachable |  C3002 |  25A |

TRIAC PWM 1-10V DALI IP65 OUTDOOR RATED RoHS COMPLIANT CE